



## ***Switched Reluctance Traction Drive Controller***

The **SRL-400** is a low cost, reliable traction controller for 3 and 4 phase switched reluctance motors.

Special features include:

- Four Phase, Fault Tolerant Motor Construction
  - ◆ Fully compatible with Rocky Mountain Technology's line of switched reluctance motors
- Full 4 quadrant control with regenerative braking (no relay)
- Compact design with integral heatsink
- Integral DC/DC converter
  - ◆ Fully compatible with Rocky Mountain Technology's line of switched reluctance motors
- Drive Efficiency up to 97.5%

## Reliable, Switched Reluctance Technology:

- **Simple, reliable, Fail-Safe Construction:** The lack of magnets and the characteristics of the switched reluctance motor allow for reliable, high speed operation at excellent efficiency
- **High torque and efficiency:** The VSR design allows for simplification of the system design and improvement of total system efficiency
- **Regenerative capability:** The VSR motor technology is well suited for both motor and power generating applications. For electric vehicle applications, four quadrant regenerative braking dramatically improves the range
- **Wide Operating Speed Range:** The VSR motor technology is well suited operation at very high speeds. The standard motors are rated for 12,000 RPM. Special versions of the standard motors are available up to 30,000 RPM
- **Competitive with Rare Earth Brushless DC/AC Motor Technology:** The SR motor can achieve performance similar to that of state-of-the-art brushless DC/AC motors with Rare Earth magnets with the use of costly magnets
- **Size:** 14" x 22" x 8"
- **Weight:** 40 lb

## Ratings:

<b>Supply Voltage:</b>	100V – 450V input (nominal)
<b>Output Current:</b>	200A cont, 400A peak (60 sec)
<b>Commutation:</b>	digital input (hall sensors)
<b>Protection:</b>	current limit, thermal

---

**Rocky Mountain Technologies Inc.**  
PO 210  
Basin, MT 59631

Tel: (406) 552-4260  
Fax: : (406) 552-4261

e-mail: [info@RockyMountainTechnologies.com](mailto:info@RockyMountainTechnologies.com)  
web: [www.RockyMountainTechnologies.com](http://www.RockyMountainTechnologies.com)

Rev 1/2009  
Specification subject to change without notice.

